

RLS, RMS, XLJ Ball Bearing



Параметр Параметр Параметр Параметр Параметр Параметр
выбирать Расследование продукта продукта продукта продукта продукта НЕТ
1 2 3 4 5 6

0.5	1.3125	0.375	0.0315 (0.8)	7	3	RLS 4
0.5	1.625	0.625	0.0630 (1.6)	12.1	5.6	RMS 4
0.625	1.5625	0.4375	0.0315 (0.8)	10.9	5	RLS 5
0.625	1.8125	0.625	0.0630 (1.6)	12.6	5.6	RMS 5
0.75	1.875	0.5625	0.0630 (1.6)	14.2	6.6	RLS 6
0.75	2	0.6875	0.0630 (1.6)	16.5	7.8	RMS 6
0.875	2	0.5625	0.0630 (1.6)	14.4	6.6	RLS 7
0.875	2.25	0.6875	0.0630 (1.6)	19.2	9.2	RMS 7
1	2.25	0.625	0.0630 (1.6)	18.6	8.9	RLS 8
1	2.5	0.75	0.0945 (2.4)	22.1	10.6	RMS 8
1.125	2.5	0.625	0.0630 (1.6)	20.2	10	RLS 9
1.125	2.8125	0.8125	0.0945 (2.4)	30.8	15.8	RMS 9
1.25	2.75	0.6875	0.0630 (1.6)	27.7	13.9	RLS 10

RLS, RMS, XLJ Ball Bearing

1.25	3.125	0.875	0.0945 (2.4)	37.7	19.5	RMS 10
1.375	2.5625	0.5625	0.0630 (1.6)	16.6	8.5	XLJ 1.3/8
1.375	3	0.6875	0.0630 (1.6)	30.2	15.7	RLS 11
1.375	3.5	0.875	0.0945 (2.4)	45.3	23.9	RMS 11
1.5	2.6875	0.5625	0.0630 (1.6)	14.3	7.5	XLJ 1.1/2
1.5	3.25	0.75	0.0945 (2.4)	34.8	17.8	RLS 12
1.5	3.75	0.9375	0.0945 (2.4)	49.5	26.2	RMS 12
1.625	2.875	0.5625	0.0630 (1.6)	14.9	8.2	XLJ 1.5/8
1.625	3.5	0.75	0.0945 (2.4)	38.7	20	RLS 13
1.625	4	0.9375	0.0945 (2.4)	55	29.9	RMS 13
1.75	3	0.5625	0.0630 (1.6)	21.8	12.2	XLJ 1.3/4
1.75	3.75	0.8125	0.0945 (2.4)	42.7	22.3	RLS 14
1.75	4.25	1.0625	0.0945 (2.4)	59.5	32.7	RMS 14
1.875	3.1875	0.625	0.0630 (1.6)	22.7	13.1	XLJ 1.7/8
1.875	4	0.8125	0.0945 (2.4)	50.5	27.8	RLS 15
1.875	4.5	1.0625	0.0945 (2.4)	69	38.7	RMS 15
2	3.3125	0.625	0.0630 (1.6)	22.7	13.1	XLJ 2